



AiP4558

Dual Low-Noise Operational Amplifier

Product Specification

Specification Revision History:

Version	Date	Description
2019-03-A1	2019-03	New
2019-07-A2	2019-07	Modify the order information
2020-03-A3	2020-03	Add SIP8 package information
2021-06-A4	2021-06	Add SOP8 (W) package information
2021-09-A5	2021-09	Modify the typical operating current value (25℃) in the Electrical Characteristics
2021-11-B1	2021-11	Change the product model
2022-01-B2	2022-01	Modify the order information
2022-03-B3	2022-03	Modify the voltage range
2023-02-C1	2023-02	Update the template



Contents

1、General Description.....	1
2、Block Diagram And Pin Description	3
2.1、Block Diagram	3
2.2、Pin Configurations.....	3
2.3、Pin Description.....	3
3、Electrical Parameter	4
3.1、Absolute Maximum Ratings.....	4
3.2、Recommended Operating Conditions.....	4
3.3、Electrical Characteristics	4
3.3.1、Electrical Characteristics	4
4、Typical Application Circuit	5
4.1、Application circuit.....	5
5、Package Information	6
5.1、DIP8	6
5.2、SOP8	7
5.3、SIP8	8
5.4、SOP8(W).....	9
6、Statements And Notes	10
6.1、The name and content of Hazardous substances or Elements in the product	10
6.2、Notes	10



1、General Description

The AiP4558 provides two independent, high-gain and internal frequency-compensated general-purpose operational amplifiers. It can operate with either a single power supply over a wide voltage range or dual power supplies. The internal frequency compensation ensures the stable work of the circuit without external components. The wide common-mode input voltage range and latch-up performance make the circuit suitable for voltage followers, DC gain components, industrial controls and all common operational amplifiers.

Features:

- Wide common-mode and differential voltage range
- No frequency compensation required
- Low power
- No latch-up
- Unit gain bandwidth: 3MHz (typical)
- Gain and phase matching between amplifiers
- Low noise: $8 \text{ nV}/\sqrt{\text{Hz}}$ (typical)
- Package information: SOP8/DIP8/SIP8/SOP8(W)

**Ordering Information:****Tube packing specifications:**

Part number	Packaging form	Marking code	Tube quantity	Boxed tube quantity	Boxed quantity	Notes
AiP4558 SA8.TB	SOP8	AiP4558	100 PCS/tube	100 tube/box	10000 PCS/box	Dimensions of plastic enclosure: 4.9mm×3.9mm Pin spacing: 1.27mm
AiP4558 DA8.TB	DIP8	AiP4558	50 PCS/tube	40 tube/box	2000 PCS/box	Dimensions of plastic enclosure: 9.2mm×6.4mm Pin spacing: 2.54mm
AiP4558 SIP8.TB	SIP8	AiP4558	25 PCS/tube	60 tube/box	1500 PCS/box	Dimensions of plastic enclosure: 19.2mm×6.5mm Pin spacing: 2.54mm
AiP4558 SW8.TB	SOP8(W)	AiP4558	96 PCS/tube	80 tube/box	7680 PCS/box	Dimensions of plastic enclosure: 5.17mm×5.22mm Pin spacing: 1.27mm

Reel packing specifications:


Part number	Packaging form	Marking code	Reel quantity	Boxed reel quantity	Notes
AiP4558SA8.TR	SOP8	AiP4558	4000PCS/reel	8000PCS/box	Dimensions of plastic enclosure: 4.9mm×3.9mm Pin spacing: 1.27mm

Note: If the physical information is inconsistent with the ordering information, please refer to the actual product.





2、Block Diagram And Pin Description

2.1、Block Diagram



2.2、Pin Configurations



2.3、Pin Description

Pin No.	Symbol	Description
1	1OUT	channel-1output
2	1IN-	channel-1 negative input
3	1IN+	channel-1 positive input
4	V _{CC-}	negative power
5	2IN+	channel-2 positive input
6	2IN-	channel-2 negative input
7	2OUT	channel-2 output
8	V _{CC+}	Positive power



3、Electrical Parameter

3.1、Absolute Maximum Ratings

Parameter		Symbol	Conditions		Rated value	Unit
supply voltage		V _{CC}	-		40 or ±20	V
differential input voltage		V _{ID}	-		±36	V
input voltage		V _I	-		36	V
thermal resistance	DIP8	θ _{JA}	-		110	°C/W
	SOP8		-		160	
	SIP8		-		110	
ambient temperature		T _{amb}	-		-40 to 85	°C
operating virtual junction temperature		T _J	-		150	°C
storage temperature		T _{stg}	-		-65~150	°C
soldering temperature		T _L	10s	SIP	245	°C
				DIP	250	
				SOP/SOP(W)	260	

3.2、Recommended Operating Conditions

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V_{CC}	-	3	-	36	V
common-mode voltage	V_{CM}	-	0	-	$V_{CC}-2$	V
ambient temperature	T_{amb}	-	-40	-	85	$^{\circ}\text{C}$

3.3、Electrical Characteristics

3.3.1、Electrical Characteristics

($V_{CC+}=15\text{V}$, $V_{CC-}=-15\text{V}$, $T_{amb}=25^{\circ}\text{C}$, unless otherwise specified)


Parameter	Symbol	Conditions	T_{amb}	Value			Unit
				Min.	Typ.	Max.	
input offset voltage	V_{IO}	$V_O=0\text{V}$	25 $^{\circ}\text{C}$	-	0.5	6	mV
			full range	-	-	7.5	
input offset current	I_{IO}	$V_O=0\text{V}$	25 $^{\circ}\text{C}$	-	2	200	nA
			full range	-	-	300	
input bias current	I_{IB}	$V_O=0\text{V}$	25 $^{\circ}\text{C}$	-	150	500	nA
			full range	-	-	800	
common mode voltage	V_{ICR}	-	25 $^{\circ}\text{C}$	± 12	± 14	-	V
maximum output voltage swing	V_{OM}	$R_L=10\text{K}\Omega$	25 $^{\circ}\text{C}$	± 12	± 14	-	V
		$R_L=2\text{K}\Omega$	25 $^{\circ}\text{C}$	± 10	± 13	-	V
unit gain bandwidth	B1	-	full range	-	3	-	MHz
input impedance	Ri	-	25 $^{\circ}\text{C}$	0.3	5	-	M Ω
large signal differential voltage amplification	AVD	$V_O=\pm 10\text{V}$, $R_L\geq 2\text{K}\Omega$	25 $^{\circ}\text{C}$	20	300	-	V/mV
			full range	15	-	-	
common-mode rejection ratio	CMRR	-	25 $^{\circ}\text{C}$	70	90	-	dB
power supply voltage rejection ratio	KSVR	$V_{CC}=\pm 9$ to $\pm 15\text{V}$	25 $^{\circ}\text{C}$	-	30	150	$\mu\text{V}/\text{V}$




equivalent input noise voltage	V_n	AVD=100, $R_S=100\Omega$, $f=1\text{KHz}$, BW=1Hz	full range	-	8	-	$nV/\sqrt{\text{Hz}}$
supply current	I_{CC}	$V_O=0V$, no load	25°C	-	3.6	5.6	mA
			full range	-	-	6.6	
crosstalk attenuation	V_{O1}/V_{O2}	open-loop	25°C	-	85	-	dB
		AVD=100		-	105	-	dB
rise time	t_r	$R_L=2K\Omega$, $C_L=100pF$, $V_I=20mV$	-	-	0.13	-	us
overshoot	-	$R_L=2K\Omega$, $C_L=100pF$, $V_I=20mV$	-	-	5	-	%
slew rate	SR	$R_L=2K\Omega$, $C_L=100pF$, $V_I=10V$	-	1.1	1.7	-	V/us

4、Typical Application Circuit

4.1、Application circuit






**5、Package Information****5.1、DIP8**

2023/12/A	Dimensions In Millimeters	
Symbol	Min	Max
A	3.00	3.60
b	0.36	0.56
c	0.20	0.36
D	9.00	9.45
E	6.15	6.60
e	2.54	
eA	7.62	9.30
L	3.00	—




5.2、SOP8



2023/12/A	Dimensions In Millimeters	
Symbol	Min.	Max.
A	1.35	1.80
A1	0.05	0.25
A2	1.25	1.55
D	4.70	5.10
E	5.80	6.30
E1	3.70	4.10
b	0.306	0.51
c	0.19	0.25
e	1.27	
L	0.40	0.89
θ	0°	8°




5.3、SIP8



2023/12/A	Dimensions In Millimeters	
Symbol	Min	Max
A2	2.70	2.90
A3	1.35	1.45
b	0.48	0.56
B1	1.20	
c	0.25	0.29
D	19.10	19.30
e	2.54	
E	11.20	11.60
E1	6.40	6.60
L1	1.30	1.70



5.4、SOP8(W)



2023/12/A Symbol	Dimensions In Millimeters	
	Min.	Max.
A	—	1.95
A1	0.10	0.18
A2	1.75	1.90
A3	0.78	0.82
b	0.33	0.47
c	0.20	0.24
D	5.00	5.25
E	7.85	7.98
E1	5.16	5.26
e	1.27	
L	0.60	0.70
L1	1.31	
θ	0°	8°



6、Statements And Notes

6.1、The name and content of Hazardous substances or Elements in the product

Part name	Hazardous substances or Elements									
	Lead and lead compounds	Mercury and mercury compounds	Cadmium and cadmium compounds	Hexavalent chromium compounds	Polybrominated biphenyls	Polybrominated biphenyl ethers	Dibutyl phthalate	Butylbenzyl phthalate	Di-2-ethylhexyl phthalate	Diisobutyl phthalate
Lead frame	○	○	○	○	○	○	○	○	○	○
Plastic resin	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
The lead	○	○	○	○	○	○	○	○	○	○
Plastic sheet installed	○	○	○	○	○	○	○	○	○	○
explanation	○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard. ×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements.									

6.2、Notes

We recommend you to read this chapter carefully before using this product.

The information in this chapter is provided for reference only and i-Core disclaims any express or implied warranties, including but not limited to applicability, special application or non-infringement of third party rights.

This product is not suitable for critical equipment such as life-saving, life-sustaining or safety equipment. It is also not suitable for applications that may result in personal injury, death, or serious property or environmental damage due to product malfunction or failure. I-Core will not be liable for any damages incurred by the customers at their own risk for such applications.

The customer is responsible for conducting all necessary tests i-Core's application to avoid failure in the application or the application of the customer's third party users. I-Core does not accept any liability.

The Company reserves the right to change or improve the information published in this chapter at any time. The information in this chapter are subject to change without notice. We recommend the customer to consult our sales staff before purchasing.

Please obtain related materials from i-Core's regular channels and we are not responsible for its content if it is provided by sources other than our company.

In case of any conflict between the Chinese and English version, the version is subject to the Chinese one.